

SunSwitch

Automatic Solar Level Switching Device

The SunSwitch can be used for any application where you need to switch depending on the solar intensity. It is an autonomous working unit that supplies itself with power from the PV-module on its rear side.

ORDER INFORMATION

- **Item no.:** 19-000050 **product name:** SUN SWITCH Light-Sensor

FEATURES

- Trouble free operation
- Pump will only run when minimum flow rates or pressure levels can be achieved which are required by certain applications
- Reduced wear on the pump and motor since the pump only starts when it will continue to run

TECHNICAL DATA

- Contact rating:
 - Max. voltage 250 VAC / 220 VDC
 - Max. current 2A
 - Max. power 60 W / 62.5 VA
- Enclosure class: IP54
- Cable length: 4 m
- Wire size: 3x 1.0mm² or AWG 18, waterproofed
- Mounted close to the solar array
- Manual with further information is available in PartnerNet
- Meets the requirements for CE

DIMENSION/WEIGHT

- Packaging dimensions: 230 x 115 x 90 mm
9.1 x 4.5 x 3.5 in
- Total weight: 1.2 kg / 0.6 lbs



BERNT LORENTZ GmbH
 Siebenstuecken 24, 24558 Henstedt-Ulzburg, Germany
 Tel +49 (0)4193 8806-700, www.lorentz.de

Sun. Water. Life.

All specifications and information are given with good intent, errors are possible and products may be subject to change without notice. Pictures may differ from actual products depending on local market requirements and regulations.